

Building Confidence with Validation at JPL

Jahning Woo, JPL
Melissa Winter, PRICE Systems
Milana Wood, JPL

NASA Cost and Schedule Symposium 2018 August 16, 2018



Disclaimer

The presentation is a description of a cost estimation study and not an endorsement of any vendor. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not constitute or imply its endorsement by the United States Government or the Jet Propulsion Laboratory, California Institute of Technology.

Overview

- Background
- Overview
- Goals
- Validation Process
- Missions
- Source of Data
- Validation Criteria
- Results
- Conclusion

Background





- NASA was one of PRICE Systems' first customers in 1975
 - We have teamed up on many calibration and validation studies over the years
- PRICE provides a tool called TruePlanning, which is a platform for many predictive cost models, including the PRICE Hardware, Systems and Software Catalogs used for this validation project
- In the last few years the PRICE Cost Research Team has added hundreds of Space data points for estimating projects such as this
 - Over 1700 Structure/Electronics calibrations added to the Equipment Type Wizard, including "Unmanned Space-Planetary" and "Unmanned Space-Earth Orbiting" Operating Environments

Overview

- The main goal was to establish a consistent methodology for using TruePlanning to estimate JPL flight projects
- The team initially selected five projects to validate, and then expanded the study to include a total of ten JPL flight projects






















Goals

Six objectives:

- Validate TruePlanning 2016 against actual costs
- Establish a repeatable process for estimating JPL flight project costs in TruePlanning
- Provide recommended mapping for System and Assembly costs objects to NASA Standard WBS
- Document results and communicate to end-users
- Standardize guidance to ensure application of the tool is consistent across JPL flight projects
- Provide guidance to external entities when model is used for assessing JPL flight projects

Validation Process



Missions Validated

| Mission | In-House or Subcontracted S/C | Deep Space | Mission Target Body | Number of Instruments | Mission Risk Class | Mission AO/Directed |
|-------------|-------------------------------------|------------|---------------------|--------------------------|-----------------------|------------------------|
| Dawn | Subcontracted | Yes | Comet | 3 | В | AO |
| Deep Impact | Subcontracted | Yes | Comet | 2 | В | AO |
| GRAIL | Subcontracted | No | Moon | 2 | В | AO |
| Juno | Subcontracted | Yes | Jupiter | 8 | В | AO |
| Kepler | Subcontracted | No | Earth-Trailing | 1 | В | AO |
| MRO | Subcontracted | Yes | Mars | 7 | В | Directed |
| MSL | In-House | Yes | Mars | 11 | В | Directed |
| NuSTAR | Subcontracted | No | Low Earth Orbit | 1 | D | AO |
| SMAP | In-House | No | Earth Observing | 1 | С | Directed |
| WISE | Subcontracted | No | Sun Synchronous | 1 | С | AO |

Source of Data


- Primary source was Cost Analysis Data Requirements (CADRe)
- CADRe Part C was used as source of cost data and schedule
- Missions modeled in TruePlanning to the CADRe Part B technical description
- CADRe Part A was consulted for further fine tuning
- Utilized TruePlanning Hardware Catalogue and Equipment Type Calculators

Validation Criteria

- The criteria for successful validation was for each project to model within 30% of actuals
- 30% represents percentage attributed to model uncertainty experienced at the early formulation stage
- This model uncertainty is in line with the average growth experienced by projects during development
- Deltas between TruePlanning and project actuals are as follows:

$$Delta \% = \frac{\text{(TruePlanning Output Cost - Project Cost Actuals)}}{\text{Project Cost Actuals}} \times 100$$


Study Results: Mission Level



| Mission | Total Delta |
|---------|-------------|
| NuSTAR | 7% |
| WISE | 6% |
| Kepler | 2% |
| SMAP | -17% |
| MSL | -5% |
| GRAIL | -21% |
| Deep | 8% |
| Impact | |
| Juno | -7% |
| Dawn | -4% |
| MRO | -1% |

Average % -3%


WBS 01, 02, 03



| Mission | WBS 01, 02, 03 Total |
|-------------|----------------------|
| | Delta |
| NuSTAR | 19% |
| WISE | 16% |
| Kepler | -27% |
| SMAP | -4% |
| MSL | 7% |
| GRAIL | -21% |
| Deep Impact | -15% |
| Juno | 4% |
| Dawn | -31% |
| MRO | 9% |

Average % -4%


WBS 05 Payload



| Mission | WBS 05 Payload Delta |
|-------------|-------------------------|
| NuSTAR | -6% |
| WISE | -8% |
| Kepler | 11% |
| SMAP | -19% |
| MSL | 3% |
| GRAIL | -28% |
| Deep Impact | 12% |
| Juno | 8% |
| Dawn | 10% |
| MRO | 11% |

| Average % | -1% |
|-----------|-----|
|-----------|-----|


WBS 06 + 10 Spacecraft and Project I&T



| Mission | WBS 06 and 10 Delta |
|-------------|------------------------|
| NuSTAR | 18% |
| WISE | 21% |
| Kepler | 6% |
| SMAP | -19% |
| MSL | -7% |
| GRAIL | -19% |
| Deep Impact | 12% |
| Juno | -16% |
| Dawn | -1% |
| MRO | -7% |

| Average % -1/0 |
|----------------|
|----------------|

Instruments



| Mission | Validated Instruments | % Delta from Project |
|---------|---------------------------------|----------------------|
| NuSTAR | Telescope (2 flight units) | -2% |
| WISE | Telescope | -16% |
| Kepler | Photometer | 8% |
| SMAP | Radar/Radiometer | -21% |
| MSL | MastCam/MAHLI/MARDI | -22% |
| MSL | ChemCam | -25% |
| MSL | CheMin | 1% |
| MSL | SAM | 6% |
| GRAIL | LGRS | -26% |
| GRAIL | MoonKam | 1% |
| Juno | JEDI | 8% |
| Juno | MAG | 5% |
| Juno | Waves | 21% |
| Juno | JADE | 28% |
| Juno | MWR | -29% |
| Juno | UVS | 9% |
| Juno | JunoCam | -16% |
| Dawn | GRaND | -12% |
| Dawn | Framing Camera/VIR contribution | 22% |
| MRO | OpNav | 18% |
| MRO | MCS | 30% |
| MRO | MARCI | -19% |
| MRO | HiRISE | 0% |
| MRO | CRISM | 3% |
| MRO | CTX | -22% |

Conclusion

- The study established a repeatable process for estimating JPL flight projects in TruePlanning
- Results are consistent with the levels of uncertainty seen in proposals and the early formulation work
- Project Level Specific Adjustments to System and Assembly Cost
 Objects should be used to capture differences in project complexity or
 implementation approach in order to provide a representative estimate
 for a new project with such variations.
- In the future, additional data points can be added to the study, to expand the scope of the validation.

Acronyms

| CADRe | Cost Analysis Data Requirements |
|-------|---------------------------------|
| H/W | Hardware |
| PBS | Product Breakdown Structure |
| QTY | Quantity |
| S/C | Spacecraft |
| S/W | Software |
| TP | TruePlanning |
| WBS | Work Breakdown Structure |
| | |

Contributors

Jet Propulsion Laboratory, California Institute of Technology
4800 Oak Grove Drive
Pasadena, California 91109

Jahning.R.Woo@jpl.nasa.gov

PRICE® Systems, LLC 17000 Commerce Parkway, Suite A Mount Laurel, NJ 08054

Melissa.Winter@pricesystems.com

Jet Propulsion Laboratory, California Institute of Technology
4800 Oak Grove Drive
Pasadena, California 91109
Milana.K.Wood@jpl.nasa.gov



jpl.nasa.gov